

RETROFIX™

Led Products produced by Breda Lighting International

Lightbase LED Industry Light 5000 K

BREDA
LIGHTING
INTERNATIONAL

120



Hang height
till 24m

Hang height
till 12m

Hang height
4-10m

10-120°
beam angle

High Power

Low Power
High Power

Low Power

Specificaties / Specifications:

Low Power
4.870 - 38.975
LUMEN
40-320W

High Power
56.930 - 110.020
LUMEN
490-960W

PHILIPS
Xitanium
LED Driver

Lumiled
Luxeon
3030 Leds

Modular
system

Prices and
Delivery times
on request

IP67
SK I
IK10

Power Factor
0,97

Operating Temp.
-40°C ~ +50°C

1-10V
Dimmable
Dali available

Optical
Lens System

5 year
Warranty
100.000h

Producttoepassingen / Product applications:

5000K

Magazijn
Warehouse

Aanlichting
gebouwen
Illuminating
buildings

Productie
Production



Lightbase®
Low Power
Industry Light



Lightbase®
High Power
Industry Light



LED Wattage	Lumen/Watt (LED chips)	Lumens	Leds	Weight (kg)	Lifetime (L70)
40W	120	4.870 lm	18	4.60	100.000 h
80W	120	9.640 lm	36	4.97	100.000 h
120W	120	14.660 lm	54	6.10	100.000 h
160W	120	19.070 lm	72	7.01	100.000 h
200W	120	23.820 lm	90	8.80	100.000 h
240W	120	28.5900 lm	108	10.13	100.000 h
280W	120	33.410 lm	126	10.96	100.000 h
320W	120	38.975 lm	144	12.23	100.000 h

LED Wattage	Lumen/Watt (LED chips)	Lumens	Leds	Weight (kg)	Lifetime (L70)
490W	120	56.390 lm	216	19.63	100.000 h
640W	120	74.070 lm	288	23.21	100.000 h
800W	120	92.100 lm	360	27.45	100.000 h
960W	120	110.020 lm	432	30.72	100.000 h