

15



## G4 Long Life Led Tube


125.000 h - 130 LM/W

### Specificaties / Specifications:

<b>130</b> LM/W*	<b>120 cm</b> 2470 LUMEN* <b>19W</b>	<b>150 cm</b> 3120 LUMEN* <b>24W</b>	<b>150 cm</b> 3640 LUMEN* <b>28W</b>	<b>125.000 h</b> Lifetime	
<b>CRI 80&gt;</b> (90> available)	Power Factor <b>0,93 - 0,96</b>	Cap Base G13 Rotatable	<b>100%</b> Flicker-Free	Operating Temp. -40°C ~ +50°C	<b>7 year**</b> Warranty

### Producttoepassingen / Product applications:

3000-3500K 4000-4500K 6000-6500K	Magazijnen Warehouses	Productie Production	Schade-herstel
--	--------------------------	-------------------------	----------------




**120 cm**  
Valtavallo G4

**150 cm**  
Valtavallo G4

RetroFix™ Wattage	Length	Lumen	Lumen/ Watt	TL Wattage (incl CVSA)	Energy saving	Saving	Lifetime
19W	1200 mm	2470	130	43W	25W	58%	125.000 h

RetroFix™ Wattage	Length	Lumen	Lumen/ Watt	TL Wattage (incl CVSA)	Energy saving	Saving	Lifetime
24W	1500 mm	3120	130	70W	46W	66%	125.000 h
28W	1500 mm	3640	130	70W	42W	60%	125.000 h



Product dimensions	A1	A2	A3	D1	D2
Valtavallo LED 120 cm	1198	1205	1212	25	27
Valtavallo LED 150 cm	1498	1507	1514	25	27

\* Lumens are nominal values. Capacity and Lumens have a tolerance of +/- 5-10%.  
 \*\* 7 Year Warranty: operating hours: ≤14 hours a day / 6 days per week. Max. 35 degrees Celsius.