


Valopaa LED Street/Wall Light
 3000-3500 / 4000-4500 / 6000-6500 K

01



Specificaties / Specifications:

VP 100 15.000 LUMEN 100W	VP 70 10.500 LUMEN 70W	VP 40 6.000 LUMEN 40W	VP 25 3.750 LUMEN 25W	10 year Warranty 100.000h	PHILIPS Titanium LED Driver
Adjustable Beam Angle with lenses	Power Factor 0,98	IP66 RAL 9006	Operating Temp. -35°C ~ +50°C	Lumiled Luxeon Z ES LED	

Producttoepassingen / Product applications:

3000K 4000K 6000K	Openbare weg Public road	Parkeer terrein Parking	Walls Buildings	Easy and Quick Installation
--	--	---	----------------------------------	--



10-12m
Valopaa
 100W Street Light

LED Wattage	Installation Height	Lumen (LED chips net)	Lumen/Watt (LED chips)	Conventional Wattage*	Energy saving	Saving	Lifetime (L70)
100W	till 12m	10.000 (15.000)	100 (150)	275W	175W	64%	100.000 h (480.000 h)

5-8m
Valopaa
 70W Street Light

LED Wattage	Installation Height	Lumen (LED chips net)	Lumen/Watt (LED chips)	Conventional Wattage*	Energy saving	Saving	Lifetime (L70)
70W	till 8 m	7.000 (10.500)	100 (150)	275W	205W	75%	100.000 h (480.000 h)

4-6m
Valopaa
 40W Street Light

LED Wattage	Installation Height	Lumen (LED chips net)	Lumen/Watt (LED chips)	Conventional Wattage*	Energy saving	Saving	Lifetime (L70)
40W	4-6 m	4.000 (6.000)	100 (150)	125W	85W	68%	100.000 h (480.000 h)

4-6m
Valopaa
 25W Street Light

LED Wattage	Installation Height	Lumen (LED chips net)	Lumen/Watt (LED chips)	Conventional Wattage*	Energy saving	Saving	Lifetime (L70)
25W	4-6 m	2.500 (3.750)	100 (150)	77W	52W	68%	100.000 h (480.000 h)

Product dimensions	Weight	L	B	H
LED VP 100	6.5 kg	590	222	73
LED VP 70	6.5 kg	590	222	73
LED VP 40	6.5 kg	590	222	73
LED VP 25	6.5 kg	590	222	73

* Capacity of Mercury Vapour lamp