

TABLE OF CONTENTS VENTILEREN

Ventilators

301



TABLE OF CONTENTS VENTILEREN



VENTILATION

Americ® VAF3000B 300mm Ventilator



Americ® VAF3000B fan for 230V.

- 305 mm (12") outlet
- Dual-wall structure
- Portable and stackable
- Both outgoing and extracting air flow
- 3 year warranty

Technical specifications:

- Voltage: 230V 50Hz
- Power: 0.75 kW
- Air outlet: 300mm (12")
- Weight: 14.7kg
- Air displacement: 4200m3 per hour
- Height: 533mm
- Length: 432mm
- Width: 355mm

Product nr	Description	Packing
72.43.03010	Americ® VAF3000B 300mm (12") diameter industrial ventilator 230V.	1

Americ® VAF8000A 500mm Ventilator



Americ® VAF8000A fan for 230V.

- 500mm (20") outlet
- Dual-wall structure
- Both outgoing and extracting air flow
- Lifting eyelet
- 3 year warranty

Technical specifications:

- Voltage: 230V, 50Hz
- Power: 3.73 kW
- Air outlet: 500mm (20")
- Weight: 54kg
- Air displacement: 16,940m3 per hour
- Height: 698mm
- Length: 698mm
- Width: 647mm

Product nr	Description	Packing
72.43.08010	Americ® VAF8000A 500mm (20") diameter industrial ventilator 230V.	1

Americ® VAF3000P 305mm Pneumatic Ventilator



Americ® AF3000P – Pneumatic 305mm industrial ventilator against dangerous sparking. Our energy-efficient, high-performance motor is totally enclosed, giving you the assurance to work safely.

- 3 year warranty
- Voltage 230V, 50Hz
- Air Consumption 3.505 m3/uur
- CFM rating of 2,063 (58.4 m3/min)
- Weighs only 12.7 kg
- Stackable to save storage or work space area
- Powerful 1.1 kW pneumatic motor
- Capability to connect up to 38 m of straight duct
- Redirects stale compressed air away from the main air stream

Product nr	Description	Packing
72.43.03050	Americ® VAF3000P 305mm (12") diameter industrial ventilator 230V	1



VENTILATION

Americ® air ducts



Air ducts for Americ® fans with Quick Connect clamp.

Americ air duct hoses are made of flexible, light duty vinyl, woven polyester.

Each of the ducts are easily retractable and designed to handle large volumes of air at relatively low pressure. In addition, they are flame-retardant and easily connect to fan lips for positive and/or negative air flow. This yellow polyester ducting is flame retardant and is UL listed for UL94-V0, meaning it is self-extinguishing, and passes the most stringent UL94 rating level for this characteristic.

Temperature Range: -29°C to 82°C.

The disposable air ducts (prod. nr. 72.43.25050) can only be used at the emitting side.

Product nr	Description	Packing
72.43.11225	Air duct 300mm x 7,5m (12" x 25') with Quick Connect.	1
72.43.12025	Air duct 500mm x 7,5m (20" x 25') with Quick Connect.	1
72.43.25050	Disposable air duct 300mm x 150m (12" x 500') not-flame retardant.	1
72.43.11227	Static conductive hose 300mm x 7,5m (12" x 25') with Quick Connect	1

Americ® ducts couplers



Connectors for Americ® air ducts.

Product nr	Description	Packing
72.43.30012	Americ® ducts coupler 300mm Ø (galvanized steel).	1
72.43.30020	Americ® ducts coupler 500mm Ø (galvanized steel).	1
72.43.30112	Americ® ducts coupler 300mm Ø (aluminum).	1

